

92X92X25 mm

JF0925-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

| SPECIFICATIONS |           |                   |                       |                |                                        |                |                     |                    |                       |             |            |
|----------------|-----------|-------------------|-----------------------|----------------|----------------------------------------|----------------|---------------------|--------------------|-----------------------|-------------|------------|
| Model          | Bearing   | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH <sub>2</sub> O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Current (Amp) | Noise (dBA) | Weight (g) |
| JF0925-1UR     | B, H      | 12                | 10.2 ~ 13.8           | 67.65          | 0.204                                  | 3500           | 0.35                | 4.20               | 0.42                  | 41.9        | 81         |
| JF0925-1SR     | B, H, S   |                   |                       | 60.75          | 0.172                                  | 3200           | 0.31                | 3.72               | 0.32                  | 38.9        |            |
| JF0925-1H      | B, H, S   |                   |                       | 52.04          | 0.139                                  | 2800           | 0.25                | 3.00               | 0.35                  | 35.1        |            |
| JF0925-1M      | B, H, S   |                   |                       | 46.31          | 0.115                                  | 2500           | 0.17                | 2.04               | 0.20                  | 32.0        |            |
| JF0925-1L      | B, H, S   |                   |                       | 38.64          | 0.080                                  | 2100           | 0.13                | 1.56               | 0.16                  | 27.6        |            |
| JF0925-1E      | B, H, S   |                   |                       | 30.86          | 0.054                                  | 1700           | 0.09                | 1.08               | 0.10                  | 23.1        |            |
| JF0925-2UR     | B, H      | 24                | 20.4 ~ 27.6           | 67.65          | 0.204                                  | 3500           | 0.23                | 5.52               | 0.24                  | 41.9        |            |
| JF0925-2SR     | B, H, S   |                   |                       | 60.75          | 0.172                                  | 3200           | 0.18                | 4.32               | 0.18                  | 38.9        |            |
| JF0925-2H      | B, H, S   |                   |                       | 52.04          | 0.139                                  | 2800           | 0.15                | 3.60               | 0.19                  | 35.1        |            |
| JF0925-2M      | B, H, S   |                   |                       | 46.31          | 0.115                                  | 2500           | 0.11                | 2.64               | 0.15                  | 32.0        |            |
| JF0925-2L      | B, H, S   |                   |                       | 38.64          | 0.080                                  | 2100           | 0.08                | 1.92               | 0.13                  | 27.6        |            |
| JF0925-2E      | B, H, S   |                   |                       | 30.86          | 0.054                                  | 1700           | 0.06                | 1.44               | 0.07                  | 23.1        |            |
| JF0925B4HR     | Dual Ball | 48                | 40.8 ~ 60.0           | 52.04          | 0.139                                  | 2800           | 0.09                | 4.32               | 0.09                  | 35.1        |            |
| JF0925B4MR     |           |                   |                       | 46.31          | 0.115                                  | 2500           | 0.08                | 3.84               | 0.08                  | 32.0        |            |
| JF0925B4LR     |           |                   |                       | 38.64          | 0.080                                  | 2100           | 0.06                | 2.88               | 0.06                  | 27.6        |            |
| JF0925B4ER     |           |                   |                       | 30.86          | 0.054                                  | 1700           | 0.05                | 2.40               | 0.05                  | 23.1        |            |

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

