

DC AXIAL FAN

JAMICON®

50X50X10 mm

DF0510-22 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
DF0510-5HR	B S H F	5	4.25~5.75	13.87	0.151	5000	0.38	1.90	1.90	30.6	17
DF0510-5MR				9.84	0.090	4000	0.18	0.90	0.90	26.7	
DF0510-5LR				5.75	0.005	3000	0.12	0.60	0.60	23.2	
DF0510-1SR		12	10.2~13.8	13.87	0.150	6000	0.24	2.88	2.88	35.8	
DF0510-1HR				12.56	0.124	5000	0.20	2.40	2.40	30.6	
DF0510-1MR				8.76	0.088	4000	0.12	1.44	1.44	26.7	
DF0510-1LR		24	20.4~27.6	5.62	0.064	3000	0.10	1.20	1.20	23.2	
DF0510-2SR				13.87	0.150	6000	0.13	3.12	3.12	35.8	
DF0510-2HR				12.56	0.124	5000	0.10	2.40	2.40	30.6	
DF0510-2MR				6.76	0.088	4000	0.08	1.92	1.92	26.7	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".
Please contact us for detail if your request bearing system is not shown in the above list.

JAMICON FAN PERFORMANCE CURVES

① 3000RPM ② 4000RPM ③ 5000RPM ④ 6000RPM

