

DC AXIAL FAN

JAMICON®

92X92X25 mm

KF0925-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS											
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0925-1TR	B	12	10.2 ~ 13.8	83.56	0.355	4400	0.48	5.76	0.54	48.5	100
KF0925-1UR				72.92	0.293	4000	0.33	3.96	0.42	45.9	
KF0925-1SR				60.14	0.200	3300	0.23	2.79	0.28	40.5	
KF0925-1HR	B, S			53.00	0.160	2900	0.16	1.91	0.24	36.7	
KF0925-1MR				47.80	0.130	2600	0.12	1.44	0.15	33.7	
KF0925-1LR				42.00	0.100	2300	0.09	1.08	0.10	30.5	
KF0925-1ER	B	24	20.4 ~ 27.6	33.28	0.070	1900	0.07	0.84	0.08	21.8	
KF0925-2TR				83.56	0.355	4400	0.26	6.24	0.29	48.5	
KF0925-2UR				72.92	0.293	4000	0.18	4.32	0.24	45.9	
KF0925-2SR	60.14			0.200	3300	0.10	2.40	0.15	40.5		
KF0925-2HR	B, S			53.00	0.160	2900	0.08	1.92	0.12	36.7	
KF0925-2MR				47.80	0.130	2600	0.07	1.68	0.10	33.7	
KF0925-2LR		42.00	0.100	2300	0.05	1.20	0.08	30.5			
KF0925-2ER				33.28	0.070	1900	0.04	0.96	0.07	21.8	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

